



MAIN APPLICATIONS

Riblene MR 10 R BA is suitable for injection moulding and compound applications and recommended for large complex mouldings, artificial flowers and low thickness articles. Thanks to its fluidity, the resin can be used as base for masterbatches. Parts made by Riblene MR 10 R BA are characterised by a high flexibility.

PROCESSING NOTES

Processing conditions are depending on several parameters: the shape of the part to be manufactured, the localisation of the injection point, the injection moulding machine and the cooling of the mould.

STORAGE AND HANDLING

Riblene MR 10 R BA is supplied in pellet form. This material may readily be conveyed and bulk fed through equipment designed for conventional pelletized polyethylene resin, provided the equipment is designed to prevent accumulation of the fines and dust particles that are contained in all polyethylene resins. These fines and dust particles can, under certain conditions, pose an explosion hazard. We recommend that the conveying system used be equipped with filters of adequate size, operated and maintained in such a manner to ensure that no leaks develop and earthed adequately. We further recommend that good housekeeping should be practiced throughout your facility. The product should be stored in dry conditions at temperatures below 50 °C and protected from sunlight. Improper storage can initiate degradation which results in odor generation, color changes and can have negative effects on the physical properties of the product. Before using this product, it is recommended to read and understand the relevant Safety Data Sheet.

AVAILABILITY

Contact the Versalis sales office nearest to you regarding availability and your specific application requirements.

FOOD CONTACT STATUS

Riblene MR 10 R BA complies with the rules and regulations of the European Union, as well as other countries, regarding the use of plastic materials in food contact applications. Certificates of compliance are available upon request.

TECHNICAL MANAGEMENT DC

Ca d Sb Ep and Am

JfgUgGd5

<UX CW AUbhc U
DUUnU6c% % JUHUfWc%((*% AUbhcU AB hUm
&+ GUb8cbUhcAUbgA hUm h - +*)& ;+*)*&
h-;)&&
h-;)&&
;)&)

North Europeand ROW

JfgUgGd5

()' %Fcih x 8ibg 7G& AUf(W)-&- 8igg&ff Ghf%'
8ibfei : fUbW *)+*9gWVcfb8ihgWUbX
h ' %&*& h(-)%(&)*%

IMPORTANT: dUgWcbgihhf UbhgUhm&hUghcfacf&UX&faUhcBhbcfaUhcBub&hUdfgbh&UfhchVghccifbckX
hfiUb&WwifUUhVihbckUffUbhmcfiUFUbh ldfgg&fad&gaU&cfcgUbmUVhmUWwDh&hfgdWhhch igcgiWbcfaUhcBub&hUfUgUg
gUUUvhdcfc&UFUbh&igcfUWdfc&W&hcb&Ubx

DISCLAIMER: hghgcfgdcbgVhmchbX igfhc&abhgUhm hfiUhcfmWcadUbwUgkUghhWbWUgihU Vhmchdfc&Whcfh
bhb&ddWUhcBhdfc&Wghcbhb&X&igba&W&U&gUb&UfaUWhWUddWUhcBgfUgU&bgUfgdcbgVhm Ub&WUbbchV&W
bWUgcgibhUVc abhcb&ddWUhcBgf

bhUfUm&