



RIBLENE® MP 20 BCA

LDPE
Low density polyethylene bio circular attributed



SUSTAINABILITY

The product Riblene MP 20 BCA 'Bio Circular attributed' is a highly sustainable LDPE produced using bionafta from renewable raw materials together with traditional raw materials. In order to attribute the sustainable feedstock component to the final product Versalis applies the Mass Balance approach, a recognized methodology that allows to trace the flow of materials along the value chain and to assign the sustainability characteristic of the raw material to the final product on a documentary basis. Riblene MP 20 BCA provides the same chemical composition and physical-mechanical performance of the traditional grade, in addition is accompanied by a sustainability declaration that certifies the share of bio attributed product. It is a high fluidity low-density polyethylene suitable for injection moulding, compound and masterbatch applications. The production of Riblene MP 20 BCA allows to contribute to the circular economy, since the bionafta used derives from waste from industrial processing of organic substances (e.g. used cooking oils). Riblene MP 20 BCA will be bio circular attributed for 100%. The exact amount of 'bio circular attributed' product will be reported in the sustainability certificate issued upon the delivery of the product.

MAIN PROPERTIES

Resin Properties	Value	Unit	Test method
Melt Flow Rate (190 °C/2.16 kg)	8	g/10min	ISO 1133
Melt Flow Rate (190 °C/5 kg)	-	g/10min	ISO 1133
Melt Flow Rate (190 °C/21.6 kg)	-	g/10min	ISO 1133
Density	0.921	g/cm ³	ISO 1183
Melting Point	108	°C	Internal Method
Brittleness temperature	<- 75	°C	ASTM D 746
Vicat softening point (1 kg)	88	°C	ISO 306/A
Mechanical Properties *	Value	Unit	Test method
Tensile stress at yield	10	MPa	ISO 527
Tensile stress at break	-	MPa	ISO 527
Tensile strain at yield	-	%	ISO 527
Flexural modulus	130	MPa	ISO 178
Hardness Shore A	-	Shore A	ISO 868 A
Hardness Shore D	48	Shore D	ISO 868 A

(*) Values are referred to injection moulded specimens. Actual properties are typical and may vary depending upon operating conditions.
R= Made in Ferrara (Italy)



MAIN APPLICATIONS

Riblene MP 20 BCA is suitable for injection moulding, masterbatch and compound applications and recommended for houseware, toys, lids and medium thickness articles. Parts made by Riblene MP 20 BCA are characterised by a high flexibility.

PROCESSING NOTES

Processing conditions are depending on several parameters: the shape of the part to be manufactured, the localisation of the injection point, the injection moulding machine and the cooling of the mould. Typical processing conditions: Temperature profile of the barrel (°C): 160 - 200 Temperature of the mould (°C): 10 - 30

STORAGE AND HANDLING

Riblene MP 20 BCA is supplied in pellet form. This material may readily be conveyed and bulk fed through equipment designed for conventional pelletized polyethylene resin, provided the equipment is designed to prevent accumulation of the fines and dust particles that are contained in all polyethylene resins. These fines and dust particles can, under certain conditions, pose an explosion hazard. We recommend that the conveying system used be equipped with filters of adequate size, operated and maintained in such a manner to ensure that no leaks develop and earthed adequately. We further recommend that good housekeeping should be practiced throughout your facility. The product should be stored in dry conditions at temperatures below 50 °C and protected from sunlight. Improper storage can initiate degradation which results in odor generation, color changes and can have negative effects on the physical properties of the product. Before using this product, it is recommended to read and understand the relevant Safety Data Sheet.

AVAILABILITY

Contact the Versalis sales office nearest to you regarding availability and your specific application requirements.

FOOD CONTACT STATUS

Riblene MP 20 BCA complies with the rules and regulations of the European Union, as well as other countries, regarding the use of plastic materials in food contact applications. Certificates of compliance are available upon request.

TECHNICAL MANAGEMENT DC M H M B

C S E A

lj wxf qnx X3u3F3

M f i Tknhj
Unf €€Ct qi w6n1
755><X s I tsf ytrhf sj xj - Bnyf q-
yj q3 08> 57: 7587>>= 08> 57: 759 77; 7
yj q3 08> 57: 759 755: 0 8> 57: 75875<7
08> 57: 759 7>=9

Mantova
Via Taliercio 14 - 46100 Mantova (MN) - Italy
tel. +39 0376305520 4 08> 58<; 85: ; 75

_, .i,yW ..., yf €uc`h

lj wxf qnx X3u3F3

9: @Nzj i j x zsj x2 Hx755;5 H w ~hp : >7<
Izsp j wzj Kf shj
yj q8887=78: : 6; 4 088 87=78: : 67

Izj xq qi twjv68
;: <; 5 Jxhngtvs Ylj zyxnqf si
yj q 09> 6: 69 57; 5: ; 6

Z^a`ceReKuqj f xj htsxzqy ynf syj kf kj y- i f yf xnj j y ktwrtvj i j yf nqj i nsktwrfynt3 Ynj nsktwrfynt3 fsi i f yf wj xj syj i nj wjns f wj yt ynj gj x
yvj fsi fhhzw yj gzy st | f w f sy- twl z f w f syj j l j } wj xj i twruqj i l nxr f i j stwxf s- qnfjgnjtk-xzhjnsjt w f h ym w f s j h y f y f j w f qnx
nxf { f nqf gqj yt w t { n i j ynj l z f w f syj j i { f qz j xktw j f h m u t i z h y t s i j r f s i

VZd T E ^ V Kny nx ynj xtqj vj xutsxngnqn z x j k w y n j j s j i w n s j y n j x f k j y - 1 y n j v j l z q f y t w - h t r u q n f s h j f x | j g n q n y n j k y j n s m f z p z k t w y n j
n s y j s i j i f u a q n h f y n t s 3 Y n j w t i z h y n x s t y n s y s i j i k t w z x j n s r j i n h f q i j { n h x f s i u n f w f h j z y n h f q f u a q n h f s y n t s s e f y w f q m x d j h q n g i j k f q q v j u t
n s h f x j t k z x j n s y n j 2 j g y j t s j i f u a q n h f y n t s x 3